



// TOURING · RENTAL · HUB-CONNECT

RH PRO

HUB-CONNECT TOURING LED

TOURING · FESTIVAL · INDOOR / OUTDOOR

Fewer cables, faster load-ins – the touring wall built around the connection.

Touring-grade LED built around HUB-connect power and signal distribution and tool-free module service. Indoor and high-brightness outdoor variants share the same 500-series cabinet standard, so one inventory covers the whole season.

P1.9 – P3.9

PIXEL PITCH

7,680 Hz

REFRESH

≤ 5,000

NITS OUTDOOR

Tool-Free

SERVICE

100k hrs

LIFESPAN

PERFORMANCE // HIGHLIGHTS

- ▶ HUB-connect power and signal cuts cable runs and load-in time
- ▶ Tool-free lock/unlock module service — no additional tools
- ▶ Indoor IP40 and outdoor IP65 variants, 4,000 – 5,000-nit adjustable outdoor output
- ▶ 500 × 500 / 500 × 1000 mm cabinets at 7.5 / 13 kg
- ▶ Camera-safe refresh up to 7,680 Hz for broadcast and IMAG

TECHNICAL SPECIFICATIONS

ENVIRONMENT	Indoor / Outdoor
PIXEL PITCH	P1.9 – P2.9 indoor · P2.6 – P3.9 outdoor
BRIGHTNESS	800 – 1,200 nits indoor · 4,000 – 5,000 outdoor
CABINET	500 × 500 / 500 × 1000 mm · 7.5 / 13 kg
REFRESH RATE	3,840 – 7,680 Hz
GRAY SCALE	10 – 16 bit
VIEWING ANGLE (H/V)	160° / 140°
IP RATING	IP40 indoor / IP65 outdoor
SERVICE ACCESS	Tool-free lock/unlock
EXPECTED LIFESPAN	100,000 hours
WARRANTY	2-year, US-based service

// OUTSIDE THE BOX DISTRIBUTION

52 O'Neil Street, Easthampton, MA 01027
US warehouse · MA showroom by appointment

// SALES CONTACT

Aaron Diamond — Director
info@outsidetheboxdistribution.com
(631) 764-4601

// AVAILABILITY

Factory-direct, made-to-order (~60-day lead) · US
fast-ship inventory rolling out · 2-year US-based
warranty

POWERED BY 4LIFE ENTERTAINMENT · OUTSIDETHEBOXDISTRIBUTION.COM · SPECIFICATIONS SUBJECT TO CHANGE